



Steel & Aluminium Carriers

Enduring Value for Your Demanding Business

Vulcan Steel & Aluminum Carriers are designed to meet the demands of our highly competitive industry. An industry where reliability, value and high quality are essential. The Vulcan Carriers are packed with practical, quality features like the popular Vulcan Wheel Lift System. Best of all, the Vulcan Carriers are backed by an extensive network of service professionals.

Call 1-800-489-2401 for more information on the Steel & Aluminum carrier series or the complete line of Vulcan quality towing and recovery equipment.

Note: Some optional equipment may be shown. Other Vulcan Towing and Recovery Equipment is available from your local Vulcan Distributor

VULCAN STEEL & ALUMINUM CARRIERS - STANDARD FEATURES

Lighted Dual Controls	Mud Flaps
Mechanical Tilt Lock Out System	FMVSS Lighting
4 Ton Winch 2/50' of 3/8" Winch Cable	Free Spool Handle
Full Length Slide Pads	Install Kit
Dual Outboard Holddown System	Cable Level Winder
Full Height Cab Protector	Cable Roller Guide
Front Chain Trays	Hydraulic Pump
Dual Lift Cylinders	2 Safety Chains
6 Tie Downs	

Back to Top

VULCAN STEEL & ALUMINUM CARRIERS - OPTIONAL EQUIPMENT

Independent Strapless Wheel Lift System	L arms in lieu of wheel retainers
Safety Lighting	Switch Panel
Wheel Simulators	Tool Compartments
P.T.O.	"V" Bridle
Tie Down Chains	Removable Rails
Additional Crossmembers (Steel Only)	Stationary Cab Protector (Requires 10" Additional C.A.)

[Back to Top](#)**VULCAN STEEL & ALUMINUM CARRIERS - SPECIFICATIONS**

DESCRIPTION	ALUMINUM			HEAVY DUTY STEEL		
	17 1/2'	19'	21'	17 1/2'	19'	21'
Outside Bed Width	95"	95"	95"	95"	95"	95"
Bed & Body						
Capacity-Distributed Load	8,000 lbs.	10,000	10,000 lbs.	8,000 lbs.	10,000	10,000 lbs.
Bed Size	17' 6"	lbs. 19'	21'	17' 6"	lbs. 19'	21'
Bed Surface	Aluminum Alloy Extrusion			Steel Diamond Plate		
Cab to Axle						
Conventional	108"	118"/122"	138"/142"	108"	118"/122"	138"/142"
Cabover	112"	127" *	144"/150"	112"	127" *	144"/150"
Recommended Chassis						
GVW Minimum	10,000	15,000	15,000	10,000	15,000	15,000
GVW Maximum	15,000	25,500	25,500	15,000	25,500	25,500
Tow Bar						
Lift Rating (lbs.)	2,000	2,000	2,000	2,000	2,000	2,000
Tow Rating (lbs.)	5,000	5,000	5,000	5,000	5,000	5,000
Independent Wheel Lift						
Lift Rating (lbs.)	N/A	2,500	2,500	N/A	2,500	2,500
Tow Rating (lbs.)	N/A	6,250	6,250	N/A	6,250	6,250

* A 19.6" body is available and recommended for cabover chassis with a 127" CA.

[Back to Top](#)

Note: Ratings are based on structural factors only--not chassis capacity. Load rating is based on equally distributed load over entire bed surface; i.e., water level load.

Vulcan reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability.