

ENDURING VALUE FOR YOUR DEMANDING BUSINESS



← **VULCAN 10 SERIES** carriers are packed with practical features to provide safe and easy hauling of a variety of loads and built with the same quality you've come to expect out of all Vulcan products. Your choices include 19', 19'6" or 21' decks in steel or aluminum with solid or removable side rails and even your choice of headboards and removable rails in steel or aluminum. Best of all, the 10 series independent hydraulic wheel lift with Vulcan's patented strapless hook-up system for fast, easy and safe towing.

VULCAN 15 SERIES, available in steel with standard removable side rails or in aluminum. The 15 series is designed to handle the increased payload of heavier GVW chassis with 22.5 tires. Available in deck lengths of 19', 21' or 22' with a capacity of 15,000 lbs. Vulcan's 15 series has the strength and durability to stand up to your tough demands. The independent wheel lift is available with Vulcan's strapless hook-up or may be ordered with a dock stabilizer for industrial use. →



Vulcan has the angle for your extreme loading situations. Introducing the Vulcan Extreme Angle option available on Vulcan 10 series carriers with solid side rails.



← Throw away the wood planks and ramps, simply release the bed lock and the rear deck section hinges down to a 6° load angle for low clearance vehicles.

With the front wheels on the rear deck section, the deck can be leveled out and the vehicle winched onto the forward section of the deck overcoming any clearance problems between the vehicle and the main deck. →



For low clearance rear bumpers or exhausts the rear deck can be lowered a second time for increased rear clearance while completing the loading or unloading process. →



Vulcan's Extreme Angle is like having two beds in one, a straight conventional carrier for most of your needs or an angled approach carrier when encountering low clearance vehicles.

Some optional equipment shown.

Standard Features:

- Platform Available in Aluminum or Steel
- Safety Chains
- Full-Length Nylatron Slide Panels
- Two Lift Cylinders
- One Extension Cylinder
- Right and Left Chain Trays
- Front and Rear Tie-Down Slots
- Bed Lock-Down System
- Bed Anti-Tilt Feature
- Removable Side Rails (15 Series Steel)
- Solid Tube Side Rails (Aluminum & 10 Series Steel)
- 8,000 lb. Hydraulic Winch with 50' of Cable
- Winch Clutch Release
- Winch Guide Rollers
- Winch Cable Tensioner
- Left and Right Hand Illuminated Controls
- Back-Up Lights
- Federal Standard 108 Lighting
- Back-Up Alarm
- Hydraulic Independent Wheel-Lift System
- Vulcan Strapless Wheel Lift Hook-Up System (Standard on 10 Series; Optional on 15 Series).
- Wheel-Lift Safety Pin
- Vulcan Mud Flaps
- Hydraulic Pump
- Full Height Steel Headboard
- Steel Beds Painted in Black Acrylic Enamel
- Pre-Assembled and Factory Tested

Optional Equipment:

- PTO
- Optional Steel or Aluminum Tool Compartments Available for Right or Left Hand Sides
- Switch Panel
- Light Bar
- Work Lights (Rear or Winch Mount)
- Spotlights (Directional)
- V-Chain Assembly
- Tie-Down Chain Assembly
- Removable Side Rails (N.A. on 15 Series Aluminum)
- Aluminum Removable Side Rails (N.A. on 15 Series Aluminum)
- Smooth Floor Instead of Diamond Plate (Steel Only)
- Additional Cross Members (Steel Only)
- Optional Color on Side Rails & Top of Deck (Steel Only)
- Extreme Angle Option (Steel 10 Series Only)
- 102" Body Width
- Dock Stabilizer in lieu of Wheel Lift
- Trailer Ball for Wheel Lift
- Planetary Winch in lieu of Worm Gear Winch
- 10,000 or 12,000 lb. Winch
- Lanyard Control for Winch
- Steel Stationary Headboard (Requires 10" additional C.A.)
- Aluminum Headboard in lieu of Steel
- Factory Installation

Bed Specifications:

	10 Series	15 Series
Platform Length	19', 19'6" & 21'	19', 21' & 22'
Load Rating	*10,000 lbs.	*15,000 lbs.
Platform Thickness	3/16" Aluminum or Steel	
Crossmembers (Steel Only)	2"x2" on 8" Centers	2 1/2"x2 1/2" on 8" Center
Crossmembers (Aluminum)	2 5/16" on 4" Centers	3" on 4" Center
Overall Width	96"	96"
Inside Width	91.5"	91.5"
Controls	5 Spool Mono-Black Valve	
Winch Rating (1 st layer)	8,000 lbs.	
Cable Diameter and Length	3/8" x 50'	

*Platform Rating is based on equally distributed load

Wheel-lift Specifications:

	10 Series	15 Series
Lift Rating at Full Extention	3,000 lbs. (2,000 lbs. for under 19,000 G. V. W.)	3,500 lbs.
Tow Rating at Full Extention	6,250 lbs. (5,000 lbs. for under 19,000 G. V. W.)	6,250 lbs.

Chassis Recommendations:

	10 Series	15 Series
Minimum G. V. W.	15,000	25,500
Maximum G. V. W.	25,500	28,000
Recommended Tire Size	16"-19.5"	22.5"
Minimum Height from Ground to Top of Frame	34"	40"
Maximum Height from Ground to Top of Frame	39"	44"

CAB TO AXLE

19'	120"
19'6"	127"
21'	144"
22'	156"



EQUIPMENT COMPANY, INC.

8503 HILLTOP DRIVE
 OOLTEWAH, TN 37363
 (800) 489-2401 • FAX (800) 960-6667
 Website: www.millerind.com

Note: Specifications subject to change without notice. All ratings specified are based on structural factors only, not vehicle capacities or capabilities.

DISTRIBUTED BY: