

# CENTURY 3212

LEGENDARY LEADERSHIP

This could be one of the most versatile units in your fleet. The Century 3212 is designed with the capability of towing a wide range of vehicles, from passenger cars, vans, city tractors and motor homes. With multi-position rear jacks, dual 15,000 lb. planetary winches and a 16 ton recovery boom, the 3212 is more than just another tow truck. This unit was designed to handle a wide variety of recovery jobs including side pulls. At last a medium duty towing and recovery unit with the same features found in Century's Heavy Duty Models.



36" Aluminum Saddle Box and other popular options shown



# CENTURY 3212

## WRECKER SPECIFICATIONS

- Retracted 30° ..... 16 tons
- Extended 30° ..... 6 tons
- Maximum angle ..... 36°
- Maximum hook height ..... 160"
- Reach past tailboard at 30° & full extension ..... 54"

## UNDERLIFT SPECIFICATIONS

- Fully retracted (with forks) ..... 12,000 lbs.
- Fully extended (with forks) ..... 8,500 lbs.
- Extended or retracted with "L" arms ..... 6,000 lbs.
- Underlift reach to center of fork holder ..... 81"
- Positive tilt ..... 20°
- Negative tilt ..... 10°

The 3212 comes standard with a low profile crossbar with removable ends, 3 sets of lift forks, fork holders, and 6,000 lbs. pivoting "L" arm system.



A Lanyard Control for boom and underlift functions is located in the compartment on the passenger side. The two front compartments provide fork storage and adjustable shelves along with an optional 24" or 36" saddle box with a large tunnel space for additional storage.



## WINCH SPECIFICATIONS

- Planetary winches ..... 15,000 lbs.
- Cable ..... 1/2" x 150' 6 x 37 IWRC
- Spring cable tensioner & air free spool

## STANDARD FEATURES

- 84" Aluminum modular body with 3 compartments per side
- Lift fork storage & chain rack, passenger & driver side
- Manual control station on drivers side
- Passenger side lanyard control for underlift & recovery boom
- Mud flaps
- 3 sets of lift forks
- Rubber fenderettes
- Safety chains
- Door closures
- Federal standard 108 lighting
- LED Body lighting
- Dual hydraulic pump
- Hydraulic rear jacks with flipper feet
- 6,000 lb. "L" arms with pivoting receivers
- "D" Rings
- Tool compartment lighting
- Spring loaded Cable Tiebacks



Manual controls for all hydraulic functions along with winch air free spools are provided on the driver's side.

The Cable on the 3212 allows the cable to be run through a snatch block and hooked to a clevis at the base end of the boom for side pull applications.



## OPTIONAL FEATURES

- Airshift PTO
- Light bar
- LED smart lights kit
- In-cab controls
- Additional lifting attachments
- Installation
- Underlift tail board controls
- 24" or 36" Aluminum saddle box
- Work lights
- Steel light pylon
- Wide load light bar
- Air & electrical hookups
- Chain kits

## CHASSIS RECOMMENDATIONS

- GVWR ..... 25,000-31,000 lbs.
- Maximum frame height ..... 38"
- Cab to Axle (clear)
  - Minimum ..... 84"
  - Maximum ..... 120"
- Tire Size Maximum ..... 255/70 R 22.5

NOTE: Specifications subject to change without notice. All ratings specified are based on structural factors only, not vehicle capacities or capabilities.

# CENTURY®

The #1-Selling Brand of Towing & Recovery Equipment Worldwide

Job 45503 5M ©6/04 Miller Industries Towing Equipment Inc. All Rights Reserved.

**Miller**  
INDUSTRIES  
TOWING EQUIPMENT INC.

8503 Hilltop Drive • Ooltewah, TN 37363  
PHONE (423) 238-4171 • (800) 292-0330  
FAX (423) 238-5371  
www.millerind.com

DISTRIBUTED BY: