



Ideally suited for high-volume towing, impound and repossession work, the Midnight Express is designed to be fast, easy and safe to operate. The driver can function the boom and hydraulic wheel lift from the safety and convenience of the cab and even pick up parallel parked vehicles at a 90° angle. Always remember to use your safety straps, safety chains, and tow lights before towing. Call 1-800-292-0330 or contact your local Century distributor for more information on the answer to high-volume towing the fast and easy way, the *Midnight Express* by Century.

Note: Some optional equipment may be shown. Contact your local Century Distributor for a complete line of Century Towing and Recovery Equipment.

CENTURY® Midnight Express

STANDARD FEATURES

- Clutch Pump
- Integrated Boom & Wheel Lift System
- Century Express Hydraulic Hookup
- In-Cab Four Function Remote Control
- 1 Pair of Safety Straps
- Safety Chains in Rear Pockets
- Tool Compartment, Left and Right Side
- Light Pylon
- Adjustable Width Steel Modular Body
- Removable Access Plate on Deck for Hydraulic Valve Service
- Power Boom Elevation with Holding Valve
- Federal Standard #108 Light Group
- Wiring Harness with Junction Box
- Mud Flaps
- Back-Up Alarm
- Power Fold for Stinger Storage
- All Components for Complete Installation
- Lubrication Fittings on all Shafts and Other Moving Parts
- Replaceable Bushings on all Major Pivots
- Cable Tensioner (301 Midnight only)
- Self Centering Crossbar with 3" Pivot Pin
- Pre-assembled and Tested
- Trailer Hitch Attachment

OPTIONAL FEATURES

- Composite Modular Body (Available in Red, White, Blue or Gray Primer)
- Switch Panel
- Motorcycle Attachments
- Front Push Bumper
- Work Lights
- 24" Tool Compartment for 84" C.A.
- Many Other Popular Options

WHEEL LIFT RATING & SPECIFICATIONS

- Lift Rating (Extended) 4,000 lbs.
- Tow Rating (Extended) 7,500 lbs.
- Retracted Distance from Tailgate at Normal Tow Position 50"
- Extended Distance from Tailgate at Loading Position. 73"
- Tow Hitch Rating 5,000 lbs.

WINCH & CABLE RATING (301 Midnight)

- Rating (First Layer of Drum) 8,000 lbs.
- Diameter and Length 3/8" x 100'
- Type 6 x 19 Hemp Center, IPS

BOOM RATINGS

- At Boom Swivel. 8,000 lbs.



TRUCK RECOMMENDATIONS

The *Century Midnight Express* should be installed on a chassis with a minimum GVW of 10,000 lbs., dual rear wheels and a minimum C.A. of 60". A heavy-duty spring package is recommended.

Note: Ratings are based on structural factors only - not chassis capacity. Century reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability.



Composite body and other popular optional equipment shown.

Miller INDUSTRIES **CENTURY®**
www.millerind.com

8503 Hilltop Drive
Ooltewah, TN 37363
Phone: (423) 238-4171
(800) 292-0330
Fax: (423)-238-5371

DISTRIBUTED BY: