

CENTURY®

L E G E N D A R Y L E A D E R S H I P

“WE’VE EXTENDED OUR REACH!”



**“CENTURY’S
MODEL 211 BOOM
...TOWING WILL
NEVER BE THE
SAME!”**

Century’s 211 integrated boom-wheel lift Towing and Recovery Vehicle will increase your company’s bottom line.

The 211 combines affordability with features that far surpass the competition. A wheel lift that folds into storage position for increased maneuverability and a hook-up system that incorporates lightweight pivoting L-arms are just a few of the many features that put the 211 first in its class.

SPECIFICATIONS

Model 211

8-ton Recovery boom (rated at boom swivel) with 8000 lb. hydraulic winch, 86" wide heavy duty body 60" C.A.

WINCHES

Rating (first layer of drum) 8000 lb.

CABLE

Diameter and length

(each drum) 3/8" Dia. x 75'

Type 6x19 hemp center, IPS

Working line limit 3,500 lb.

BOOM SPECIFICATIONS

Using cross bar sheave attachment

	Retracted	Extended
Lift height from ground to hook at max. Boom elevation	68"	81"
Reach past tailgate at max. Boom elevation	34"	63"
Range of Elevation	0-40°	
Boom Rating at Boom Swivel	16,000 lbs.	
Boom Rating at Crossbar Sheave Attachment	4,000 lbs.	

STANDARD FEATURES

- Lightweight Pivot L Arm System
- Safety Chains in Rear Pockets
- Tool Compartment, Left Hand Side
- Variable Speed Hydraulic Winch
- 6x19 Hemp Center IPS 3/8" x 75' Wire Rope
- 86" Wide Heavy Duty Body with 8" Sills
- PTO/Pump Combination
- Federal Standard 108 Light Group
- Wiring Harness with Junction Box
- Dual Controls • Mud Flaps
- Back Up Alarm
- Power Fold for Stinger Storage
- Cross Bar Sheave Attachment
- All Components for Complete Installation
- Lubrication Fittings on all Shafts and Other Moving Parts
- Preassembled and Tested



CENTURY®

Miller INDUSTRIES
TOWING EQUIPMENT INC.

P.O. Box 120, Ooltewah, TN 37363
Phone: (423) 238-4171 1-800-292-0330
FAX: (423) 238-5371
5M-0298

DISTRIBUTED BY:

OPTIONAL FEATURES

- Tool Compartment, Right Side
- Switch Panel
- Convenience Group
- Trailer Ball Adapter
- Light Pylon
- Wrecker Special Light Bar
- Work Lights
- Front Push Bumper
- 24" Tunnel Tool Compartment for 84" C.A.
- Cable Anti-Spooling Tensioner
- Many Other Popular Century Options

TRUCK RECOMMENDATIONS

Century Model 211 should be installed on a chassis with minimum GVW of 10,000 lbs., dual rear wheels and a minimum C.A. of 60". A heavy-duty spring package is recommended. Requires a manual transmission and at least one accessible PTO opening or optional clutch pump for automatic transmission.

MODEL 211 WHEEL LIFT SPECIFICATIONS

DESCRIPTION	POSITION	INCHES
RETRACTED DISTANCE FROM TAILGATE	At Full Down	29 3/4
	At Normal Tow Position	34
EXTENDED DISTANCE FROM TAILGATE	At Full Down	61
	At Normal Tow Position	64 3/4
CROSS BAR SPREAD	Full Retracted	60 3/4
	Full Extension	90 3/4
MAXIMUM HYDRAULIC EXTENSION		31 1/4

Lift rating 4,000 lbs. (extended)

Tow rating 7,500 lbs.

Chassis Frame cut-off 35" cut off

Approx. Weight 2200 lbs.

NOTE: Specifications subject to change without notice. All ratings specified are based on structural factors only, not vehicle capacities or capabilities.