

CENTURY®

L E G E N D A R Y L E A D E R S H I P

EB-4 SERIES



EB-4/Express
Some optional equipment shown

The Century EB-4 integrated towing & recovery units have been designed to be an ideal match for the popular lo-pro medium-duty chassis. The EB-4 series is equipped with twin 12,000 lb. winches and a recovery boom rated at 12 tons retracted and 3 tons extended. The EB-4's 84" C.A. body provides the operator with 2 spacious tool compartments per side with a tunnel on the front compartment.

The **EB-4 Series** is available in 3 models: *the EB-4/6500*, which includes Century's 3-way pivoting L-Arm System and 3" lift forks and fork holders; the **EB-4/Express**, which utilizes Century's Hydraulic Auto Load System; and the **EB-4/Express with Removable Claws** provides the versatility of a hydraulic auto-load system with the capabilities of removing the wheel claws and using the crossbar with a set of lift forks for heavier loads.



The Removable claw option on the EB-4/Express allows the wheel claws to be removed and a set of lift forks installed for conventional under-lift towing.



The EB-4/Express provides the operator with a 6,000 lb. hydraulic autoloading system. Capabilities of the EB-4/Express include the ability to tow away parallel parked vehicles by hooking-up at a 90° angle.

SPECIFICATIONS EB-4

12-ton Recovery boom (rated at boom swivel retracted) with dual 12,000 lb. hydraulic winch, 90" wide heavy-duty body, 84" C.A.

WINCHES

Rating (1st layer or drum) 12,000 lbs.

CABLE

Diameter and Length (each drum) 7/16" x 100'

Type 6x25 IWRC XXIPS

Working Line Limit 6,800 lbs.

BOOM SPECIFICATIONS

		Retracted	Extended
Main Boom	Lift height from ground to hook at max. boom elevation	94-7/16"	130-5/16"
Main Boom	Reach past tailgate at min. boom elevation	1-5/8"	61-5/8"
Main Boom	Reach past tailgate at max. boom elevation	-	25-3/4"
Range of Elevation.....		0-36.5°	
Boom Rating at Boom Swivel (Retracted).....		24,000 lbs.	
Boom Rating at Boom Swivel (Extended).....		6,000 lbs.	

EB-4/6500 UNDER LIFT SPECIFICATIONS

Description	Position	Inches
Retracted Distance from Tailgate to Centerline of Lift Forks	At Full Down	36-1/2"
	At Normal Tow Position	42"
Extended Distance from Tailgate to Centerline of Lift Forks	At Full Down	70-1/2"
	At Normal Tow Position	76"
Maximum Hydraulic Extension		34"

EB-4/6500 LIFT CAPACITIES

Underlift Position	"L" Bar Rating		Lift Fork Rating
	STD	OPT	STD
Retracted	4,000 lbs.	6,000 lbs.	9,000 lbs.
T.E.M.A.	4,000 lbs.	6,000 lbs.	7,000 lbs.
Extended	4,000 lbs.	6,000 lbs.	6,500 lbs.

Tow Rating.....20,000 lbs.

EB-4/EXPRESS WHEEL LIFT SPECIFICATIONS

Description	Position	Inches
Retracted Distance from Tailgate to rear edge of bar	At Full Down	39-1/4"
	At Normal Tow Position	45"
Extended Distance from Tailgate to rear edge of bar	At Full Down	70-1/2"
	At Normal Tow Position	76-1/4"
Maximum Hydraulic Extension		31-1/4"

EB-4/EXPRESS LIFT CAPACITIES

	Wheel Claws	Lift Fork Rating (Removable Claw Option)
	Retracted	6,000 lbs.
T.E.M.A.	6,000 lbs.	7,000 lbs.
Extended	6,000 lbs.	6,500 lbs.

Tow Rating.....20,000 lbs.

EB-4 STANDARD FEATURES

- Integrated boom & underlift system
- Variable speed hydraulic winches
- Winch Cable assemblies
- Power fold for stinger storage
- 360° directional boom end swivels
- Power boom elevation with holding valve
- Power boom extension
- Lubrication fittings on all shafts and other moving parts
- 90" wide body with 2 tool compartments per side
- Tunnel on front compartment
- Dual control stations
- 9" Sills
- Federal standard #108 lighting
- Wire harness with junction box
- Back-up alarm
- Hydraulic pump
- Safety chains with built-in pockets
- EZ service hydraulic filter
- Spring-loaded winch clutch releases
- All components for complete installation

EB-4/6500 STANDARD FEATURES

- 3" lift forks and fork holders
- Lightweight 3-way pivot L-Arm System

EB-4/EXPRESS STANDARD FEATURES

- Express Hydraulic Auto load system
- In cab lanyard control for wheel lift

EB-4/EXPRESS *with Removable Claws* STANDARD FEATURES

- Express Hydraulic Auto load system
- In cab lanyard control for wheel lift
- Removable wheel claws
- 3" lift forks and fork holders

EB-4 OPTIONAL EQUIPMENT

- Stainless Steel body option includes front tool compartments
- Additional lifting forks (EB-4/6500 or EB-4/Express with Removable Claw only)
- 6,000 lb. L-Arm Kit (EB-4/6500 only)
- Convenience group
- Trailer ball adapter
- Wrecker special light bar
- Work lights
- Light pylons
- Fiberglass fenderettes
- Cable Anti-Spooling Tensioner
- Switch panel
- Mud flaps
- Many other popular Century® options



TRUCK RECOMMENDATIONS

Model EB-4 should be installed on a chassis with minimum GVW of 17,500 lbs., dual rear wheels and a minimum C.A. of 84". A heavy-duty spring package is recommended. Chassis Frame cut-off of 38".

Note: Specifications subject to change without notice. All ratings specified are based on structural factors only, not vehicle capacities or capabilities.



TOWING EQUIPMENT

DISTRIBUTED BY:

8503 Hilltop Drive • Ooltewah, TN 37363 • www.millerind.com
PHONE (423) 238-4171 • (800) 292-0330 • FAX (423) 238-5371